




(mm)



CCpilot VA FREELY PROGRAMMABLE MULTIFUNCTIONAL 7" DISPLAY

CCpilot VA is a 7" full-colour display with a powerful ARM CPU. The open LinX software platform offers a choice of powerful tools for application development. This, together with a WVGA high brightness display and hardware accelerated 2D, 3D and vector graphics, enables fast design of premium user interfaces. With optional all-glass PCAP touch screen and configurable soft keys, operators are offered an intuitive interaction with the system.

CCpilot VA has multifunctional capability and can be used as instrumentation display, machine control HMI, video monitor, electronic manual and more.

By adding the wireless extension module CrossLink AI, featuring WiFi, modem, GNSS and Bluetooth, CCpilot VA can be used for telematics, GIS and Fleet Management functionality. **Turn for technical specifications »**

Standard models

PART NUMBER	SOFT KEYS	TOUCH SCREEN	OPTICAL BONDING
C000 134-80	•	•	
C000 134-81	•		
C000 134-82	•	•	•
C000 134-83	•		•

CCpilot VA PRODUCT SPECIFICATIONS

COMPUTING CORE	
MAIN PROCESSOR	Freescale i.MX 537, 32 Bit ARM processor. Runs freely programmable Linux system and LinX Software Suite base package.
COPROCESSOR	Runs watchdog functions controlling integrity of product, for increased reliability and safety.
STORAGE	512 MB NAND flash for operating system and applications.
RAM	512 MB DDR3
GPU	Integrated Graphics Processing Unit supporting hardware accelerated 2D, 3D and vector graphics.

DISPLAY	
TYPE	TFT with LED backlight
COVER LENS	Glass with anti-reflective treatment.
SIZE AND RESOLUTION	7" WVGA, 800 x 480 pixels
COLOR DEPTH	24 bit
CONTRAST RATIO	600:1
BRIGHTNESS*	500 cd/m ²
DIMMING	Automatic dimming through ambient light sensor. Dimming can be controlled manually via soft keys and/or touch screen.
OPTICAL BONDING	TFT and glass or touch screen optically bonded. Optical bonding is optional.

HMI	
TOUCH SCREEN	Glass cover lens with anti-reflective treatment.
SOFT KEYS	10 soft keys, configurable. Soft keys can be used as function keys for the GUI, to control Power On/Off, to control display brightness etc. Soft keys are optional.
BUZZER	Configurable buzzer for alarms and notifications.

INTERFACES	
CAN	2 x CAN, physical layer ISO11898 2.0B and J1939-11. Bitrate configurable 20 kbit/s - 1 Mbit/s.
ETHERNET	1 x Ethernet. 10/100 Base-T.
USB	2 x USB 2.0. 1 in multipin connector and 1 in mini-USB under cover on rear side.
INPUTS	8 configurable inputs for analog/digital sensors. May be used for measuring resistance/4-20mA/ frequency/digital/analog signals.
OUTPUTS	2 configurable high side outputs for driving up to 1A. May be used for continuous driver or PWM output.
POWER SUPPLY	12 or 24 VDC nominal voltage. Voltage range 9-32 VDC. CPU and communication operational down to 6,0 VDC.
KEY SWITCH	1 x Key switch input, for start-up/shut down.
VIDEO	2 x Analog Video input. NTSC or PAL.

SOFTWARE	
OPERATING SYSTEM	Linux
SOFTWARE APPLICATION PLATFORM	LinX Software Suite, basic package. Extension modules available, eg. CODESYS.

ENVIRONMENT	
IP CLASS	IP66 and IP67
EMC CONFORMITY	2004/108/EC, ISO 14982:2009, ISO 13309:2010
VIBRATIONS	IEC 60068-2-64 Random 0.02g ² /Hz 5-2000Hz 3x3h
SHOCK	IEC 60068-2-27 50 g/11ms ±3 x 3 shocks
TEMPERATURE RANGE (°C)	Operating: -30 to +70 Storage: -40 to +85

ENCLOSURE	
HOUSING MATERIAL	Reinforced nylon
MECHANICAL INSTALLATION	Panel mounting or mounting on stand/arm
CONNECTORS	3 x Deutsch DTM06-12 connectors, 1 x Mini USB

SIZE AND WEIGHT	
W x H x D (mm)	252 x 156 x 51
WEIGHT (kg)	0.65

* Typical values

crosscontrol
AN ACTUANT COMPANY

Sales contact: sales@crosscontrol.com | General: info@crosscontrol.com | www.crosscontrol.com

© 2018 CrossControl. All rights reserved. The information herein is supplied without any guarantees and can change without prior notification. Shielded cables may be necessary to fulfill industrial EMC standards. Some functionality may have limited operating temperatures. Windows are trademarks of Microsoft Corporation. Linux is the registered trademark of Linus Torvalds. Intel Atom is a trademark of Intel Corporation. Bluetooth is a trademark of Bluetooth SIG. CANopen is a registered trademark of CAN in Automation (CiA).