




(mm)



CCpilot X900 POWERFUL DISPLAY COMPUTER WITH INTEL ATOM QUAD CORE

The **CCpilot X900** is designed to address challenges created by the rapid increases in the requirements of software content in modern mobile machines. Systems for improved productivity, reduced environmental impact, safety and security are software intensive. The performance of graphical user interfaces is a key success factor for how the machine system is perceived. To efficiently realize these types of solutions, it is critical to use a platform that supports capable software frameworks and toolchains.

The X900 is based on an industrial grade quad core Intel processor which features a very powerful integrated GPU. The widely supported x86 architecture and the X900 offer the choice of a Linux or Windows 10 operating system. This means that system developers can utilize all the powerful toolchains, software components, and 3rd party applications available in either the Windows or Linux domains. The CCpilot X900

leverages current and next generation graphics APIs and frameworks, making it possible to realize and support advanced systems. The GPU and software layers support Vulkan, enabling the advantages of the new graphics backend of Qt 6. The platform utilises accessible CFAST storage for in-field expandability and storage upgrades. The CCpilot X900 enables advanced support tools, HMI solutions, business logics, guidance and control, all in one display computer solution.

The CCpilot X900's Atom based SoC is designed to support video analytics and the platform supports rapidly emerging technologies like multiple digital camera streams, and object detection.

The X900 offers these high-end computing capabilities in a ruggedised and highly reliable product design that withstands the environmental loads associated with industrial vehicle applications. **Turn for technical specifications »**

CCpilot X900 PRODUCT SPECIFICATIONS

COMPUTING CORE	
OVERVIEW	Intel quad core CPU, iGPU & coprocessor.
CPU	Intel Atom® 64 bit x5-E3940 CPU, 4 x 1.60 GHz.
GPU	400MHz Base. 144Gflops (FP32). 1.500 GPixel/s Supports advanced Graphics and computing APIs.
STORAGE	8 GB CFast MLC for Linux or 64 GB for Windows (both upgradeable)
RAM	4 GB DDR3L

DISPLAY	
TYPE	TFT with LED backlight.
COVER LENS	Tempered clear glass.
OPTICAL BONDING	Yes. Screen & cover lens optically bonded to improve sunlight readability and prevent fogging.
SIZE AND RESOLUTION	9" 15:9 WXGA resolution, 1280 x 768 pixels
COLOR DEPTH	24 bit
CONTRAST RATIO*	1000:1
BRIGHTNESS*	720 cd/m²
DIMMING	Yes, automatically controlled through the ambient light sensor or manually in steps, 1-100%.
AMBIENT LIGHT SENSOR	Yes

HMI	
TOUCH SCREEN	Projective Capacitive (PCAP) with 2-point multi-touch.
STATUS LED	RGB LED
SOUND	Yes. Configurable high quality front facing speaker (95 dBA) for alarms and audio.
SOFT KEYS	3 configurable buttons on the front of the display.

INTERFACES	
CAN	2 x CAN-FD ports, physical layer ISO 11898 2.0B. SAE J2284-1 to SAE J2284-5, Configurable bit rate. CAN and CAN-FD modes are supported.
USB	2 x USB 2.0 high speed
ETHERNET	2 x Ethernet. 10/100 Base-T
SERIAL	1 x RS232
AUDIO	1 x Line Out
POWER SUPPLY	12 or 24 VDC Nominal Voltage. Voltage range 10-34 VDC. CPU and communication operational down to 6 VDC.
KEY SWITCH	1 Key switch input, for start-up/suspend/resume/shutdown.

MECHANICAL	
HOUSING MATERIAL	Aluminium
INSTALLATION	Panel mounted or VESA 75 bracket.
CONNECTORS	3 x 5 pin DIN M12 for power and CAN ports 2 x 4 pin DIN M12 for Ethernet 2 x M12 microUSB 1 x 8 pin DIN M12 Auxiliary connection and serial port
DIMENSIONS, WxHxD (mm)	267 x 166 x 57
WEIGHT (kg)	2.0

ENVIRONMENTAL SPECIFICATION	
IP CLASS	IP65
EMC CONFORMITY	CE certified for Earth Moving equipment, Agriculture and Forestry equipment.

VIBRATIONS	IEC 60068-2-6 Sinusoidal, IEC 60068-2-64 Random.
SHOCK	IEC 60068-2-27. 30g/6ms
TEMPERATURE RANGE (°C)	Operating: -25 to +70 Storage: -30 to +80

OPERATING SYSTEM	
SYSTEM	Windows 10 or Custom Linux system based on Yocto
KERNEL	4.14.68
BSP	Available to create a custom Linux image.
COMPUTING AND GRAPHICS APIs	Advanced UX and computing tasks supported by the SoC: OpenGL 4.6, Vulkan 1.1.97, DirectX 12, OpenCL 2.1, Shader Model 6.4, OpenVG 1.1.

SOFTWARE FRAMEWORKS & TOOLS	
DEVELOPMENT ENVIRONMENT	Virtual machine or Native Linux. Windows, .net, visual studio
PROGRAMMING	Supported languages include C++, C, QML, JavaScript, Python, HTML5, IEC61131-3. Supports all PC/Windows tools and languages.
GCC COMPILER	aarch64-poky-linux-GCC 8.3.0 C++17 or newer
UI FRAMEWORKS	Supports Qt6 and Qt5. Qt Commercial is optional, enables closing access to the system. Support for Web frameworks.
WINDOWING	Windows, Weston, Qt Wayland. Direct EGLFS is available if windowing is not required.

APPLICATION PLATFORM
LinX Software Suite, open and modular platform based on Qt, common for all CCpilot display products. Examples of modules and components listed below.

GUI DESIGN
UX Designer, a pre-built virtual machine with Qt Creator, compilers, libraries, graphical components and templates.

CAN NETWORKING
Fieldbus Access, easy configuration of J1939 and CANopen networks.

ISOBUS
Universal Terminal, Task Controller and guidance.

TELEMATICS
Open platform supports configurable soft telematics controller and backend web solution.

SMART DEVICE INTEGRATION
Smart Connect, framework for building apps and integrating smart phones and tablets (service tool, secondary HMI).

REMOTE APPLICATION ACCESS
VNC server and client, web browser and server.

SOFT PLC
CODESYS 3.5

DIGITAL VIDEO
Ready-made solution for displaying digital camera streams over Ethernet. RTP, MPEG4, MJPEG, H.264 (4Kp30) and H.265.

PLATFORM SUPPORT
Below you find specifications of features for which the product platform has inherent hardware support. These are not currently available in the standard product specified above but may be added over time in the generic evolution of the product, or added for a specific, larger customer program.

TOUCH SCREEN SENSITIVITY Calibration for special use cases (i.e. gloves).

STORAGE Supports SLC memory for added reliability.

SECURITY RSA/AES, elliptic-curve cryptography, key storage, secure boot-up, signed applications, docker, virtualisation.

OS Win10 image and associated BSP/SDK. Desktop Linux distributions.

QT AUTOMOTIVE Supports Qt Automotive, with IVI applications.

DISPLAY Device hardware can support additional monitors for multi display solutions.

* Typical values



Sales contact: sales@crosscontrol.com | General: info@crosscontrol.com | www.crosscontrol.com

© 2023 CrossControl. All rights reserved. The information herein is supplied without any guarantees and can change without prior notification. Check www.crosscontrol.com for latest version. Shielded cables may be necessary to fulfill industrial EMC standards. Some functionality may have limited operating temperatures. Windows are trademarks of Microsoft Corporation. Linux is the registered trademark of Linus Torvalds. Intel Atom is a trademark of Intel Corporation. CANopen is a registered trademark of CAN in Automation (CiA).