



CCpilot V1090 10" TERMINAL FOR PROCESS CONTROL, HMI SYSTEMS & PRECISION TASKS

The **CCpilot V1090** display computer is designed to address the needs of process control & precision applications including ISOBUS terminals, 2D/3D machine control and guidance systems. Key features include a 10-inch display, robust aluminium housing, accessible USB port, audio notifications, and fast attach/detach connectors for easy removal and theft prevention. It comes with a rich interface set-up for CAN and Ethernet networking, supporting 100/1000Base-T1 and 1000Base-TX.

With a high brightness, high contrast wide XGA resolution IPS type display the CCpilot V1090 provides intuitive user interaction with multi-touch PCAP, also with gloves. This allows for concurrent visualization of multiple applications and reliable operation in harsh conditions with readability in direct sunlight aided by the optically bonded screen to reduce reflections and eliminate fogging.

The CCpilot V1090 is available with LinX, our open and modular software platform. It includes firmware and OS support, pre-packaged application toolchains for Qt and CODESYS, and application modules for commonly required functionality.

This is also a very powerful platform for OEM factory fit HMI systems. The CrossControl open software platform, and windowing framework, opens up avenues for running multiple software systems in parallel. This means that precision functionality, for example ISOBUS & guidance, can run side-by-side with commonly required HMI system features including base process control, instrumentation, vision systems and embedded manuals.

For HMI solutions in which a single display may not provide the screen real estate needed to offer a good user interface the V1090 and V1290 can support an optional display link interface for a secondary monitor in sizes 7", 10" or 12", or even a 5" display to act as a smart control pad.

Turn for technical specifications »

crosscontrol
making machines smarter, safer and more productive

The content herein is preliminary and may be subject to change without further notice.

CCpilot V1090 PRODUCT SPECIFICATIONS

COMPUTING CORE	
OVERVIEW	i.MX 8QuadXPlus, quad core CPU, integrated GPU & M4 Co-processor.
CPU	4 x Cortex A35 @ 1.2 GHz
GPU	Vivante GC7000lite high performance graphics processing unit.
STORAGE	8 GB, enhanced mode eMMC pseudoSLC.
RAM	2 GB 32 bit LPDDR4 @ 1200MHz

DISPLAY	
TYPE	IPS Type with >85° viewing angles in all directions
COVER LENS	Tempered glass with AG coating
OPTICAL BONDING	Touch screen with optically bonded cover lens
SIZE AND RESOLUTION	10.1" WXGA, 1280x800 pixels
COLOR DEPTH	24 bit, 16 million
CONTRAST RATIO*	800:1
BRIGHTNESS*	900 cd/m²
DIMMING	Yes, in steps, 1-100%
AMBIENT LIGHT SENSOR	Yes, enabling automatic dimming

HMI	
TOUCH SCREEN	Projective Capacitive with up to 10-point multi-touch. Calibrated to support interaction with gloves or be in-sensitive to water drops.
STATUS LED	RGB LED, application controlled and dimmable
BUZZER	Yes, configurable buzzer, Min 85dB @ 10 cm from front. Mic In, Line Out for cabin speakers

INTERFACES	
CAN	2 ports, physical layer ISO 11898 2:2016, ISO11783-5:2019 compatible (2ms interrupts with a capacitor). Configurable bit rate. CAN 2.0 and CAN FD compliant.
USB	USB 1 x USB 2.0 high speed
I/O	2 input, 2 output
ETHERNET	1 x 1000BASE-T, 1 x 1000BASE-T1
WI-FI	Optional. 802.11ac/a/b/g/n, dual-band 2.4/5 GHz
BLUETOOTH	Optional. Bluetooth 5.0.
POWER SUPPLY	12/24 VDC nominal, range 9-36 VDC. Power on from 4.5 Volt over DC.
KEY SWITCH	1 input for start-up/suspend/resume/shutdown

MECHANICAL	
HOUSING MATERIAL	Aluminium
INSTALLATION	4 point VESA 75 mount
CONNECTORS	Deutsch DTM06-12 for power, CAN, I/O, ignition, RS232 and Audio, M12 for Ethernet, Fakra antenna USB A socket on side.
DIMENSIONS (mm)	267 x 186 x 40
WEIGHT (g)	To be confirmed g

ENVIRONMENTAL SPECIFICATIONS	
IP CLASS	IP65/66/67
EMC CONFORMITY	2014/30/EU, ISO 14982-, ISO 11783-5:2019 (ISOBUS compliance 2ms interrupts.) ISO 11783-2:201, ISO 13766-1/2
VIBRATIONS	IEC 60068-2-64. Random, 0.02g²/Hz 5-2000Hz 3x3h
SHOCK	IEC 60068-2-27, ±25g /6ms±3 x3, 15000 total shocks

TEMPERATURE RANGE (°C)	IEC 60068-2. Operational -30°C to +70°C, 5C/ min, 1h hold time, 20 cycles. -30C and +70 C for 24 hours. Storage -40°C to +80°C
OTHER	Chemicals resistance, UV, Ball Drop Test

OPERATING SYSTEM	
SYSTEM	Custom Linux system based on Yocto 4.0+
KERNEL	5.15 (Long Term Support)
BSP	Available to create a custom Linux image
COMPUTING AND GRAPHICS APIs	Support for advanced UX and computing tasks: OpenGL ES, Vulkan, OpenCL, OpenVG
BOOTUP TIME	Configurable. Cold boot 3-7 sec, resume <1 sec

SOFTWARE FRAMEWORKS & TOOLS	
DEVELOPMENT ENVIRONMENT	Virtual machine or Native Linux.
PROGRAMMING	Supported languages include C++, C, QML, JavaScript, Python, HTML5, IEC61131-3.
GCC COMPILER	GCC C++17 or newer
UI FRAMEWORKS	Supports Qt6 and Qt5. Qt Commercial is optional, enables closing access to the system. Support for Web frameworks.
WINDOWING	Weston, Qt Wayland. X Wayland. Direct EGLFS is available if windowing is not required.

APPLICATION PLATFORM
LinX Software Suite, open and modular platform based on Qt, common for all CCpilot products. Examples of modules and components listed below.

GUI DESIGN	UX Designer, a pre-built virtual machine with Qt Creator, compilers, libraries, graphical components and templates.
CAN NETWORKING	Fieldbus Access, easy configuration of J1939 and CANopen networks.
ISOBUS	Universal Terminal
REMOTE ACCESS	VNC server and client, web browser and server.
SOFT PLC	CODESYS 3.5
DIGITAL VIDEO	Ready-made solution for displaying multiple digital camera streams over Ethernet. RTP, MPEG4, MJPEG, H.264 (4Kp30) and H.265. Support for controlling camera settings like resolution and frame rate.

PLATFORM SUPPORT
Below you find specifications of features for which the product platform has inherent hardware support. These are not currently available in the standard product specified above but may be added over time in the generic evolution of the product, or added for a specific, larger customer program.

LARGER STORAGE	Expandable up to 32 GB enhanced mode eMMC pseudoSLC. Possible to increase storage even more through Mini-PCIe card (see below).
TOUCH SCREEN SENSITIVITY	Option to have touch controller calibrated for special use cases.
SECURITY	RSA/AES, elliptic-curve cryptography, key storage, secure boot-up, signed applications, docker.
Qt AUTOMOTIVE	Supports Qt Automotive, featuring e.g. safe rendering and IVI applications.
MONITOR	Optional display link for additional monitors
EXPANSION CARDS & MODULES	Mini-PCIe boards and modules can be added for extending functionality and performance. E.g. AI/ML accelerator modules, radio and connectivity modules, storage cards.
OS IN CO-PROCESSOR	Supports use of an RTOS in the integrated Cortex-M4F companion microcontroller (co-processor). For implementation of real-time critical and safety functionality.
KEY SWITCH	Support for a second key switch for pre-ignition.
FAST BOOT	Configurable to 3 sec, System resume <1 sec

* Typical values

crosscontrol

Sales contact: sales@crosscontrol.com | General: info@crosscontrol.com | www.crosscontrol.com

© 2024 CrossControl. All rights reserved. The information herein is supplied without any guarantees and can change without prior notification. Shielded cables may be necessary to fulfill industrial EMC standards. Some functionality may have limited operating temperatures. Linux is the registered trademark of Linus Torvalds. CANopen is a registered trademark of CAN in Automation (CiA).